


320 Reed Circle • Corona, CA 92879 Tel: 951-734-4391 • FAX: 951-734-9488



TEST CERTIFICATION

Cert Date: 10/17/13 : 61815 Cert #

LOT #: 283790 MFG DATE: 07/24/13 Page:

Cust #

P.O. #: OJEY15

: 141327

P.O. Qty:

5000

Customer : B/E AEROSPACE

Ship To : MIAMI, FL.

Ship #: 1783747 Ship Qty: 4458

MFG. Part #: NASM21250-06008 REV.I

Material Spec: AMS6322N

Part #: MS21250-06008

Heat #: 10175090 Mill, Vendor: CHARTER STEEL/WIRE

Type: 8740

Code: 14078

Procure Spec: NASM8831 REV.4

Hardness per NASM1312-6, ASTM E 18 gr E 384 Minimum Requirement: 739-43 HRC.

41.0

41.0

42.0

42.0

42.0

42.0

42.0

42.0

42.0

42.0

42.0

43.0

43.0

43.0

43.0

Metallurgical Tests

Hardness: N/A

Grain Size: N/A Decarb: NONE

Metallurgical, Special Process and Subcontracted Test Information THREADS INSPECTED PER MIL-S-8879C N.3, AS8879D OR MIL-S-7742D A MACRO AND MICROSTRUCTURE SATISFACTORY 5 PCS HEAT TREAT PER AMS2759/1E BY QUALITY HEAT TREAT #131931 CAD PER AMS-QQ-P-416C TYII CL-2 BY Q.C.P. #132913 100% MAG PER ASTM E 1444/E1444M-12 BY 3V FASTENERS 10/16/13 HYDROGEN EMBRITTLEMENT PER NASM 1312-5 REV.1 BY ATLAS #107875

THIS TEST CERTIFICATION SHALL NOT BE REPRODUCED EXCEPT IN FULL WITHOUT WRITTEN APPROVAL OF 3V FASTENERS CO., INC. TESTING LABORATORY. THIS CERTIFICATION SHALL NOT BE USED BY THE CUSTOMER TO CLAIM PRODUCT ENDORSEMENT BY ANY AGENCY OF THE U.S. GOVERNMENT. 3V FASTENERS CERTIFIES THAT THE PRODUCT SHIPPED ON ABOVE PURCHASE ORDER WERE MANUFACTURED, INSPECTED AND TESTED IN COMPLIANCE WITH ALL APPLICABLE PRINTS AND SPECIFICATIONS. ALL SUPPORTING DOCUMENTATION IS ON FILE AT 3V. ACCREDITED TO AS9100C, ACCREDITED ISO 9001:2008. SAI GLOBAL CERT-0049384, CAGE CODE 1ER65, COO:USA BAE APPROVAL BAE/AG/30148/CAL, AIRBUS APPROVAL 30085. THE RAW MATERIAL USED TO MANUFACTURE THESE PARTS WAS MELTED IN THE USA OR A QUALIFYING COUNTRY AND COMPLIES WITH THE APPLICABLE SECTIONS OF DFARS 252-225.

QUALITY ASSURANCE LAB SUPERVISOR

ROBERT CANTILLO

Aerospace, BVE